

Packaging - Specification
container for transport



220l tight head drum F1 / blue /
S56x4 / S56x4

SCHÜTZ GmbH & Co.KG&A
Schützstraße 12
D 56242 Selters / Germany

date: 23.07.2008 / TE-KO / ha
page 1 from 1

Article - no.: 4012233

Technical dates:

nominal capacity	: 220,0	Litre
brimful capacity min.	: 221,0	Litre

outer height	: 935,0 +/-5	mm
outer diameter	: 581,0 +/-3	mm
bung design	: S56x4 / S56x4	

resistance against compression	: 25.000	N
characteristic number min.	: 600	N/mm

total weight without plugs	: 8,50 +0,2/-0,1	kg
total weight with plugs	: 8,56 +0,2/-0,1	kg

Material:

drum body	: PE-HD
colour	: blue
bung plug	: PP
colour	: white
gasket	: EPDM
colour	: white

Description:

body:
tight head drum, similar to TH ISO 20848-2 NC – SP 220l,
with two blow moulded bungs in the top, flat and bulged coat,
top with blow moulded "TOP"-ring.

Closure system BCS 56x4

- a) openings with female thread S56x4
 - b) plugs with male thread S56x4
- * filling bung and plug see DIN EN 20848-3

UN – marking:

- UN 1H1 / Y1.9 / 200 / ...* / BAM11407 – SCHÜTZ3
- * year of production

Note:

- 1x plug S56x4 torqued and fitted with G2 white Push Lock overseal
- 1x G2 white Push Lock overseal supplied loose
- testing and description acc. VPA 3, 4, and 8,
marking to VPA 6