Packaging - Specification


container for transport

ECOBULK SX 1000 UN "Ex" / DN150, G2-plug with vent / integr. butterfly-valve, ETFE-gasket / 2 label plates (front- and back side) / tamper shield / Steel-framepallet

SCHÜTZ GmbH & Co. KGaA
Schützstraße 12
D 56242 Selters / Germany

Date: 18.03.2002 / TE-KO / ss

Article - No.: 1073087



Technical data:

Rated volume:			1000	Litre
Overflow volume:			1050	Litre
Length:			1200	mm
Width:			1000	mm
Height with pallet:			1160	mm
Filling opening:			150	mm
Discharge opening:			50	mm
Fork opening:			100	mm
Label plate:			2	piece
Weight:	Inner container:		15,5	kg
	Total:	approx	77,5	kg

Packaging - Specification

container for transport

ECOBULK SX 1000 UN "Ex" / DN150, G2-plug with vent / integr. butterfly-valve, ETFE-gasket / 2 label plates (front- and back side) / tamper shield / Steel-framepallet

SCHÜTZ GmbH & Co. KGaA
Schützstraße 12
D 56242 Selters / Germany

Date: 18.03.2002 / TE-KO / ss

Article - No.: 1073087

Construction:	Rectangular grid box made of tubular Steel material. Zinced steel coat for protection of the PE-Innertank. Top made of zinc coated steel sheet, closed with tie-bar, label plate with Schütz-Ticket on front side, additional label plate on the back side.	
Outer Container:	Grid / Steel coat / Bottom plate /	
Material:	Steel top / Tamper shield:	Steel, galvanized against corrosion
Inner Container:	Rectangular blow molded tank of high density polyethylene (HDPE) with filling opening in the middle of the top section. Discharge opening at the bottom of the front side.	
Material:	Lupolen 4261 AG UV 60005, natural	
Filling Opening:	Filling Opening DN150 with external thread, closed with screw cap, G2-plug with vent, sealing-cap and gasket.	
Material:	Screw cap DN150:	Lupolen 4261 A, red
	O-ring gasket:	EPDM
	G2-plug:	Moplen EP 301 K
	O-ring G2-plug:	Lucalen 2710 H, natural
	Vent:	Silicone-Caoutchouc
Discharge Opening:	Integrated butterfly-valve DN50 with blue handle. Outlet sealed with an Al-lined PE-foil. Valve closed with open screw cap, PE-disk and flat-gasket. Outlet nozzle enclosed. Grounding sheet integrated in valve, conductive connected with grid.	
Material:	Housing butterfly-valve:	Lupolen 4261 A, natural
	Flat-gasket:	Dyneon ET
	Screw cap DN50:	Lupolen 3821 D, black
	PE-disk:	Lupolen 3821 D
	Flat-gasket screw cap:	Alveolit
	Outlet nozzle:	Lupolen 3821 D, natural
	Grounding sheet:	Steel, rust-free (V2A)
Pallet:	Steel-framepallet (1000 x 1200 mm), 4-way entry	
Material:	Steel, galvanized against corrosion	
Directive:	Heavy-metal free, according EU-directive 94-62-EG	
Delivery:	Ready for filling, clean	
UN-Marking:	UN 31 HA1 / Y / D / SCHÜTZ / BAM 5404 / 5230 / 1728 / 1053 l / 77 kg / 100 kPa	